

21.5" Open frame monitor

Projected Capacitive Touch and Non-Touch



Long life cycle



2-year warranty



IP65 commercial grade

Product Summary

Our 21.5" open frame touch monitor features a ultra slim and compact state-of-the-art design, with energy-saving and low-heat LED panels. Available with integrated 10-touch Projected Capacitive technologies and non-touch with protective glass. We offer various options for commercial kiosk applications including **casino gaming**, **sports betting**, **self-service** and **retail**.

Compodis's open frames can be mounted in landscape and portrait mode and come with various brackets for optimal flexibility for integrating in any table, kiosk, or cabinet design. It also comes with 3 video inputs: HDMI, Display Port and VGA, as well as audio output to reduce cabling inside a cabinet design. Global certifications that apply: CE, FCC(B), CCC(B), UL, cUL, RCM and RoHS.

- **10-touch Projected Capacitive**
- **Wide viewing angle 178° x 178°**
- **Zero bezel**
- **24/7 operation**
- **UI-60950 Antivandal & IK08**
- **Common electronics on all sizes**
- **Including VGA/USB cable and OSD board**
- **Including external power adapter**

21.5" Open frame monitor

Specifications	
Size	21.5" TFT LCD
Max resolution	1920 x 1080
Contrast Ratio	1000 x 1
Brightness (Backlight Type)	250 nits (No Touch), 225 nits (Projected Capacitive)
Touch screen	Projected Capacitive or Protective glass (Non-touch)
Touch points	10
Touch screen interface	USB-HID (Type B)
USB port	1 x USB 2.0 (Type B) for Touch Interface (USB-HID)
Video port	1 x VGA (DB15), 1 x DP, 1 x HDMI
Audio port	1 x Line-Out
Power input	1 x 12VDC Jack with lock
Power supply	36 W (12VDC, 3A) External Power Adaptor
Housing color	Black
Material	Glass, Plastic (ABS), SECC Metal
Compliance	Front Panel IP65 Compliant
Dimensions (W x H x D) mm	519.9 x 314.9 x 42.4
Net weight (kg)	4.4 kg
Gross weight (kg)	6.3 kg
Carton (W x H x D) mm	610 x 405 x 160
VESA	100 x 100 mm
Ball Drop	UL60950(500g/1.3m) and IK08
Certifications	CE, FCC(B), CCC(B), UL, cUL, RCM, RoHS
Operating Temperature	0°C ~40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 95% RH. Non-Condensing
Remote Key (optional)	1 x RJ45 (for OSD connector)

Learn more about Compodis at www.compodis.com